

KX-P3196 High Speed Forms Printer



Features:

- Easy-access bottom push tractor
- Straight paper path
- Accommodates up to 6-part forms
- High speed printing: maximum 500 cps
- Long life ribbon of approximately 12 million characters
- Parallel & Serial Interfaces
- Setup disk includes Windows™ 95, 98, 3.1x, NT 3.5x and NT 4.0 Printer Drivers

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1999 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

	Panasonic Document Imaging Company Unit of Matsushita Electric Corporation of America Computer Peripheral Division Headquarters: 2 Panasonic Way, Secaucus, NJ 07094
---	---

w w w . p a n a s o n i c . c o m / o f f i c e

KX-P3196 Specifications

Print Method	Impact Serial Dot Matrix		
Printhead and Life	(0.3 mm wire diameter), 200 mil strokes; 200 mil chr (draft)		
Print Direction	Text: Bi-directional (user selectable unidirectional) logic seeking; Graphics: Unidirectional		
Character Matrix	Draft (9x9), NLQ (18x18), HSD (8x9)		
Print Speed		Draft	NLQ HSD
	15 cpi Micron	500 cps	67 cps -
	12 cpi Elite	400 cps	80 cps 475 cps
	10 cpi Pica	333 cps	67 cps 396 cps
Printing Sizes	5,6,7.5,8.5,10,12,15,17,20 cps, &PS		
Characters Per Line	40, 48, 60, 68, 80, 96, 120, 137 & 160 cpl		
Character Sets	Epson mode: 1 Italic & 18 character set tables 15 International characters and Legal Set, IBM mode: 18 character set tables		
Bit Image (matrix)	240 x 216 dots per inch		
Line Feed Time	Approx. 52 msec. (with 1/6 inch line feeding)		
Setup Disk	3-1/2" disk controls all printer functions, Includes a command reference program and drivers for Windows™ 95, 98, 3.1x, NT 3.5x, & NT 4.0		
Tractor Feed	Push (rear & bottom), Friction (top)		
Paper Feed Path	Bottom, Rear, & Top		
Paper Specifications	Continuous 3.0 to 10.0 inches, 12 to 24 lbs.		
Copies	Up to original +5 non-carbon copies		
Thickness	Maximum thickness 0.017 in. (bottom) 0.014 in. (rear)		
Emulations	Epson FX-850, IBM Proprinter III, Oki Microline 320 Turbo (without scalable fonts)		
Interfaces	Centronics parallel & RS-232C/serial		
Buffer	64K (standard)		
Noise Level	<58 dBA in Normal Mode NLQ <56 dBA in Quiet Mode NLQ		
Environment	Operating: 41°F to 104°F, 20 to 80% humidity Storage: -4°F to 140°F, 10 to 90% humidity		
Reliability	10,000 hrs MTBF @ 25% duty cycle		
Dimensions & Weight	17.7" (w) x 15.1" (d) x 7.3" (h); 18.8 lbs.		
Power Consumption	Standby 10W; maximum 190W		
Warranty	2 Year Express Exchange Warranty See your dealer for details.		
Options & Accessories	KX-P190 Endless black fabric ribbon cassette, Life expectancy approx. 12 million character (in draft mode/rolling ASCII)		