KX-P6100 Laser Printer for Windows



The ease of use and flexibility that Windows provides when creating a document is now available when printing your work. Specially designed for Windows users, the KX-P6100 receives its print commands directly from your computer, which ultimately benefits you. No more waiting and waiting for documents to print because this 6-page per-minute printer prints 50% faster than most other traditional entry-level printers in its class. The Panasonic KX-P6100 takes printing frustration out of the picture and gives you a better window to productivity.

| Printing Method | Semiconductor Laser |
|------------------------|--|
| Print Speed | 6 pages per minute (ppm) maximum. |
| | (Letter size paper test mode, 5% image area, |
| | all originals) |
| Print Quality | 600 dpi class using Edge Enhancement |
| | Technology (EETTM) or Photo Enhancement |
| | Technology for enhanced images. |
| Resolution | 300x300 dots per inch (dpi) |
| Paper Feed | 1 Multi-purpose tray |
| Paper Weight | 16-32 lbs. |
| Paper Input | |
| Paper | Up to 100 sheets (20 lb.) |
| Labels | Up to 30 sheets |
| Transparencies | Up to 30 sheets |
| Envelopes | Up to 10 |
| Paper Output | Up to 50 sheets paper (20 lb.) |
| Software Emulation | |
| GDI Mode | Windows GDI |
| PCL Mode | HP LaserJet IIP*for DOS* applications |
| | running under Windows |
| Fonts | 2 |
| GDI Mode | UtilizesTrueType* fonts |
| PCL Mode | Courier 10 point, 12 pitch Regular, Bold and |
| | Italic Courier 12 point, 10 pitch Regular, Bold |
| | and Italic Line Printer 8.5 point, 16.66 pitch |
| | Regular |
| Interface | Bidirectional parallel |
| Consumables Life | Toner ^{1:} 1,000 pages average (4% image area |
| | with repetitive printing of 10 pages) Toner |
| | Cartridge (KX-P456) 2,000 pages average |
| | (4% image area with repetitive printing of |
| | 10 pages) Process Unit (KX-PEP2) 15,000 |
| | pages average |
| Power Consumption | 480W typical (Operating Mode) |
| | 9W typical (Power Saving Mode) |
| Dimensions | 5.2"(W) 0 14.9"(D) x 11.3"(H) |
| Weight | Approx. 14.4 lbs. |
| Noise Level | Printing 45 dBA Standby 0 dBA |
| Power Source | 10V |
| Operating Envir onment | 10 to 32.5°C (50 to 90°F), 10 to 80% RH |
| Storage Environment | 0 to 35°C (3210 95°F), 10 to 80% RH |
| Warranty | One-year exchange program in the event of |
| | defective product (excluding consumables |
| | and limited life itema). Cae dealer for detaile |

KX-P6100 Specifications

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations.

Copyright ©1997 Matsushita Electric Corporation of America. All rights reserved.

Online Spec Sheet



1- Shipped with KX-P6100.

As an Energy Star Partner, Panasonic Communications & Systems company has determined that this product meets the EnergyStar Guidelines for energy efficiency.

and limited life items). See dealer for details.