

Desk Station IV PC-PA2701U

FUNCTION: To expand external interface capabilities by using expansion cards and 5 1/4" industry standard devices.

COMPATIBILITY: T2200SX, T3300SL, T4400C, T4400SX, T4400SXC, T4500, T4500C, T4600, T4600C, T4700CS, T4700CT, T4800CT, T4850CT, T4900CT

DIMENSIONS: OVERALL: 4.4"H x 13.6"W x 15.9"D
EXPANSION SLOTS (98-pin AT-type slot w/AT type connector):
Slot One: 25.4 x 339 x 122mm (1.0" x 13.3" x 4.8")
Slot Two: 20.3 x 339 x 122mm (0.8" x 13.3" x 4.8")
EXPANSION BAY:
Maximum device size: 43 x 208 x 150mm (1.7" x 8.2" x 5.9")

WEIGHT: 15.7 lbs. NOTE: Monitor stand holds 44 lbs. maximum.

PORTS: 1 - RS232C serial port COM1(3F8H-3FFH) or COM2(2F8H-2FFH)
1 - Parallel printer port (378H-37FH, BI-DIR)
1 - FDD port
1 - analog VGA port, 15 pin
1 - PS/2 keyboard port
1 - PS/2 mouse port

POWER: AC INPUT: Voltage: 115-240V Frequency: 50-60Hz
Current: 1.8A (50Hz); 2.8 (60Hz)
DC OUTPUT: Constant voltage for operation: 21 volts, 1.9A (max)
Constant current for operation: 1.9A
EXPANSION SLOTS and 5 1/4" EXPANSION BAY:

Power	Volts	Continuous	Peak	EXP. SLOT	Drive Bay
	DC	Amps	Amps	PIN #	Connector PJ7
	+ 5V ñ5%	7.5	8.0	B03,B29,D16	4
	- 5V ñ10%	0.4	-	B05	-
	+ 12V ñ5%	2.9	5.9	B09	1
	- 12V ñ10%	0.6	-	B07	-

EXPANSION: IBM PC/AT expansion slot signals NOT SUPPORTED:

SIGNAL	PIN NUMBER	DESCRIPTION
OWS	D08	0 Wait State
DRQ0	D09	DMA Request Channel 0
DRQ7	D15	DMA Request Channel 7
-DACK0	D08	DMA Acknowledge Channel 0
-DACK7	D14	DMA Acknowledge Channel 7
IRQ15	D06	Interrupt Request Level 15